

MUNICIPAL MACHINES CATALOGUE

TRADITION QUALITY AND TRUST

W W W . P O M . C O M . P L





SWEEPERS WITH HYDRAULIC DRIVE

Tractor sweepers are designed for sweepeing and simultaneously collecting debris from flat surfaces such as roads, yards, sidewalks and more. The construction allows the sweeper to be mounted on a tractor or on popular models of front and telescopic loaders.

Hydraulically driven sweepers are simple, robust in design, efficient and reliable.

Standard equipment:

litter container with manual emptying

Additional equipment:

side brush
water sprinkling system
hydraulic emptying of litter container
front support wheel
electro valve divider
flow regulator



WWW.POM.COM.PL see more







T 801, T 801/1, T 811, T 811/1

Width	Width	Width	Width
1,6 m	2,0 m	1,4 m	1,2 m
Horizontal	Horizontal	Horizontal	Horizontal
brush speed	brush speed	brush speed	brush speed
150 rpm	150 rpm	150 rpm	150 rpm
Brush	Brush	Brush	Brush
diameter	diameter	diameter	diameter
600 mm	600 mm	600 mm	600 mm
Tractor pump	Tractor pump	Tractor pump	Tractor pump
efficiency	efficiency	efficiency	efficiency
20 - 40 l/min			
Weight	Weight	Weight	Weight
290 kg	320 kg	275 kg	260 kg

WWW.POM.COM.PL see more





SWEEPER WITH PTO DRIVE T 803/0

Thanks to its compact size, this sweeper is ideal not only for cleaning urban and industrial areas, but also for indoor use in buildings such as barns, stables and livestock facilities.

It's an excellent tool for clearing snow in winter conditions.



SWEEPERS

T 803/0 T 804/0

Width 1,2 m

Horizontal brush speed 150 rpm

Brush diameter 600 mm

PTO drive 540 rpm

Weight 105 kg Width 1.2 m

Horizontal brush speed 150 rpm

Brush diameter 600 mm

Tractor pump efficiency min. 16 l/min

Weight 110 kg

SWEEPER WITH HYDRAULIC DRIVE T 804/0

The use of a new-generation hydraulic motor in this sweeper allows it to operate efficiently even with tractors equipped with lower external hydraulic flow capacity.



see more



SWEEPERS



Modern design

T 805/1

Width 1,6 m 2,0 m

Horizontal brush speed150 rpm

Horizontal brush speed
150 rpm

T 805/2

Brush diameter600 mm

Brush diameter
600 mm

Tractor pump efficiency min. 30 l/min. **Tractor pump efficiency** min. 30 l/min.

Weight Weight 260 kg 320 kg

Dust reduction during operation

Smooth brush height adjustment

Modern system of emptying litter container

240 I litter container

Various brush types



WWW.POM.COM.PL see more

ROAD SPREADERS N 031/2, N 031/21





Motyl N 031/2 and N 031/21 municipal spreaders are equipped with dedicated municipal attachment and are designed for winter maintenance of roads, squares, parking areas and sidewalks.

They can spread salt, sand, grit or their mixtures.

During the summer season, the spreaders can also be used to spread granulate and powdered fertilizers on green areas such as lawns, sports fields and parks.

precise	The use of a transport belt at the bottom of the
•	hopper instead of a traditional gaitator ensures

even distribution of both granulate and powdered

materials

modern A modern vibration module prevents material build

up inside the hopper, ensuring even spreading and

increased work efficiency

durable High resistance to the corrosive effects of salt and

fertilizers thanks to the use of laminate and stainless steel in all components that has direct contact with

the spreading material

versatile Smooth adjustment of spreading quantity and width

allows the spreaders to be used in municipal,

agricultural and gardening applications









ROAD SPREADERS N 031/2, N 031/21

ARE AVAILABLE WITH THREE HOPPER VERSIONS

polyester laminate



acid-resistant stainless steel (INOX)



Additional equipment for N 031/2, N 031/21

hydraulic slide, canvas cover, filter mesh, vibration module road lighting

powder - coated carbon steel



see more





For the most demanding users



SANDMAN

SANDMAN N 031/2 and SANDMAN N031/21 was developed for the most demanding users, made entirely of stainless steel, including frame, tension and drive drums, covers, discs and vanes.

The use of stainless steel in the spreader's construction has eliminated its only previous drawback – insufficient corrosion resistance of the frame.

Purchasing this version means a long-term investment with no need of repainting and significant time savings on cleaning and maintenance.

Fully made of stainless steel

Municipal attachment and vibration module in standard

Additional equipment: orchard attachment







N 065 WITH GPS OR MANUAL CONTROL

Municipal spreader N 065 is designed for winter road maintenance of streets, squares, parking lots and sidewalks. It can distribute salt, sand, grit or their mixtures. During summer season spreader can be used for spreading granulate fertilizers on green areas such as lawns, sports fields and parks.

Additional equipment:

extension 400 I canvas cover with INOX frame road lighting

Hopper capacity 600 I

Hopper capacity with extension 1000 I

Maximum load capacity 1500 kg

PTO drive 540 rpm

Spreading width 1,5 - 8 mb

Weight 270 kg



MOTYL N 031/21 WITH HYDRAULIC DRIVE



Metal hopper coated with powder paint with enhanced resistance to aggressive environments

Transport belt driven by hydraulic motor

Modern vibration module for improved operation efficiency

Smooth adjustment of the transport belt`s speed

Smooth adjustment of the spreading disc`s speed

Spreading system centrifugal

Hopper capacity 600 l

Spreading width up to 20 m

Tractor pump efficiency min. 30 l/min.



Additional equipment:

hydraulic slide canvas cover road lighting municipal attachment



MOTYL N 031/2, N 031/21 WITH ELECTRO-HYDRAULIC DRIVE



Metal hopper coated with powder paint with enhanced resistance to aggressive environments

Transport belt driven by hydraulic motor

Modern vibration module for improved operation efficiency

Smooth adjustment of the transport belt's speed

Smooth adjustment of the spreading disc`s speed

Spreading system centrifugal

Hopper capacity 400 |

Spreading width up to 18 m

Tractor pump effeciency min. 16 l/min.



Standard equipment:

electronic control of spreading disc speed municipal attachment

Additional equipment:

hydraulic slide canvas cover road lighting





LIQUID PUMPING DEVICE N 406

N 406 tractor pump is versatile device designed for pumping municipal sewage, water and other liquids that may contain solid contaminants up to 15 mm in size. The pump is powered by the tractor's hydraulic system and weighs only 37 kg.

It is used in agricultural farms, land reclamation works, construction sites and emergency operations such as flood relief

Thanks to its lightweight and compact design, transportation to the work site is effortless

Hydraulic drive enables operation in any terrain, including areas without electrical power or during power cuts

High efficiency with low power consumption

Drive

hydraulic motor

Revolutions

1560 rpm

Maximum pump efficiency

1500 l/min





WWW.POM.COM.PL see more

HYDROMIST P112/0

Hydromist sprinkler is designed for watering gardens, lawns, flower beds and other surfaces. It has a large 500 liter tank allowing efficient and productive work, as well as warning LED lighting and adjustable and changeable nozzles. It is ideal for even watering large areas making the job fast and easy.

HydroMist is used not only in agriculture and gardening, but also it works perfectly at washing and spraying streets, squares and parking lots.

This type of equipment is becoming more and more popular for natural and safe spraying against ticks, mosquitoes and other troublesome insects. Adjustable nozzle height and diameter enables more effective operation which fits to conditions and surroundings.

HydroMist is equipped with ergonomic, durable, brass spray gun with a 15 meter hose, ideal for cleaning small surfaces such as traffic signs, rinsing stairs or watering flowers or garden beds.

There is also growing interest in eco-friendly liquid alternatives to road salt such as calcium chloride and magnesium chloride which are used for winter road maintenance.

The HydroMist sprinkler is perfectly suited for the efficient and environmentally friendly distribution and use of such agents.

COMFORTABLE WATERING, SPRAYING, WASHING, MAINTENANCE

Hitch

Three-point linkage cat. I and cat. II

Tank capacity 500 l

Power supply voltage

Electric pump efficiency 13.2 l/min

Spray gun hose length 15 m



The most popular product of 2025



see more





Pracowniczy Ośrodek Maszynowy w Augustowie Sp. z o. o.

4 Tytoniowa Street, 16-300 Augustów mob. +48 504 835 203, +48 515 028 027

WWW.POM.COM.PL